

## Roundsling Supra Plus/Magnum



### Product information

**Design:** Load carrying yarn covered with “seamless” color coded protection sleeve. Supra Plus and Magnum have an extra strong protection sleeve. As well as a blue label the Supra plus is provided with a RFID chip for identification.

**Stretch with working load:** 2-3%.

**Length tolerance:** Nominal length (EWL)  $\pm 2\%$ .

**Material:** Polyester. Resistant to most acids but not strong alkalizes.

**Marking:** According to standard, The slings are provided provided with a RFID chip for identification and a blue label with manufacturer's symbol, working load limit (WLL), length, CE marking and a label with handling instr

**Temperature range:** app.  $-40^{\circ}$  -  $+100^{\circ}\text{C}$ .

**Standard:** EN 1492-2

**Safety factor:** 7:1.

Part Code	WLL ton
34010010XXX0180	1
34010020XXX0180	2
34010030XXX0180	3
34010040XXX0180	4
34010050XXX0180	5
34010060XXX0180	6
34010080XXX0180	8
34010100XXX0180	10
34010150XXX0180	15
34010200XXX0180	20
34010250XXX0180	25
34010300XXX0180	30
34010400XXX0180	40
34010500XXX0180	50
34010600XXX0180	60
34010800XXX0180	80
34011000XXX0180	100

## Blueprint

