

## STOBITEX Wear Protection Sleeve PU-1/single

### Product information



Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

Also available as double sided sheathes, STOBITEX Wear Protection Sleeve PU-2/double side.

**Material:** Polyurethane.

**Temperature range:** Approx. -30° up to +70°C, short expose to approx. +90°C.

Part Code	Size	For 2 layer lifting mm	For 4 layer lifting mm	For roundslings ton	a mm	i mm	h mm	w mm	A mm	Weight kg/m	Delivery time
80255040105	50	30	-	-	50	40	10	5	-	0.85	10
8025PU15040205	50	-	30	-	50	40	20	5	-	0.9	10
8025PU17060125	70	50	-	-	70	60	12	5	-	1.25	10
8025PU17060175	70	-	50	-	70	60	17	5	-	1.3	10
8025PU18070125	80	60	-	-	80	70	12	5	-	1.3	10
8025PU18070245	80	-	60	-	-	70	24	-	80	1.35	10
8025PU18575175	85	-	-	1	85	75	12	5	-	1.35	10
8025PU19585245	95	-	-	2	95	85	24	5	-	1.5	10

8025PU1110100125	110	90	-	-	110	100	12	5	-	1.55	10
8025PU1110100175	110	-	-	3	110	100	174	5	-	1.6	10
8025PU1110100245	110	-	90	-	110	100	24	5	-	1.6	10
8025PU1145135125	145	120	-	-	145	135	12	5	-	2	10
8025PU1145135245	145	-	120	-	145	135	24	5	-	2.1	10
8025PU1170160125	170	150	-	-	170	160	12	5	-	2.3	10
8025PU1170160175	170	-	-	6	170	160	17	5	-	2.4	10
8025PU1170160245	170	-	150	-	170	160	24	5	-	2.4	10
8025PU1200190125	200	180	-	-	200	190	12	5	-	2.6	10
8025PU1200190175	200	-	-	8	200	190	17	5	-	2.65	10
8025PU1200190245	200	-	180	-	200	190	24	5	-	2.7	10
8025PU1230220365	230	-	-	10	230	220	36	5	-	3.5	10
8025PU1260250158	260	240	-	-	260	250	15	8	-	3.9	10
8025PU1290280308	290	-	-	15	290	280	30	8	-	4.4	10
8025PU1330320158	330	300	-	-	330	320	15	8	-	4.4	10
8025PU1330320308	330	-	300	-	330	320	30	8	-	4.8	10
8025PU1330320458	330	-	-	20	330	320	45	8	-	5.3	10

## Blueprint

