

## STOBITEX Wear Protection Sleeve PU-2/double side



### Product information

Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

**Design:** Single- or double sided sheathes.

**Material:** Polyurethane.

**Temperature range:** Approx. -30° - +70°C, short expose to apx +90°C.

Part Code	Code	W mm	For 2 layer lifting mm	For lashings	For 4 layer lifting mm	For webbing sling t	Weight kg	Delivery time
8025PU2666043	PU-2 66/60/4/3	3	-	50	-	-	0.85	10
8025PU25040105	PU-2 50/40/10/5	5	30	35	-	-	1.1	10
8025PU27060125	PU-2 70/60/12/5	5	50	-	-	-	1.45	10
8025PU28070125	PU-2 80/70/12/5	5	60	-	-	-	1.6	10
8025PU29585125	PU-2 95/85/12/5	5	75	75	-	-	2	10
8025PU2110100125	PU-2 110/100/12/5	5	90	-	-	-	2.1	10
8025PU2145135125	PU-2 145/135/12/5	5	120	-	-	-	2.8	10
8025PU2170160125	PU-2 170/160/12/5	5	150	-	-	-	3.4	10

8025PU2200190125	PU-2 200/190/12/5	5	180	-	-	-	3.8	10
8025PU2330320158	PU-2 330/320/15/8	8	300	-	-	-	7.2	10
8025PU2330320308	PU-2 330/320/30/8	8	-	-	300	-	7.8	10
8025PU2330320458	PU-2 330/320/45/8	8	-	-	-	20	8.4	10
8025PU25040205	PU-2 50/40/20/5	5	-	-	30	-	-	10
8025PU27060175	PU-2 70/60/17/5	5	-	-	50	-	-	10
8025PU28575175	PU-2 85/75/17/5	5	-	-	-	1	-	10
8025PU28070245	PU-2 80/70/24/5	5	-	-	60	-	-	10
8025PU29585245	PU-2 95/85/24/5	5	-	-	75	2	-	10
8025PU2110100175	PU-2 110/100/17/5	5	-	-	-	3	-	10
8025PU2110100245	PU-2 110/100/24/5	5	-	-	90	-	-	10
8025PU2145135245	PU-2 145/135/24/5	5	-	-	120	-	-	10
8025PU2170160175	PU-2 170/160/17/5	5	-	-	-	6	-	10
8025PU2170160245	PU-2 170/160/24/5	5	-	-	150	-	-	10
8025PU2200190175	PU-2 200/190/17/5	5	-	-	-	8	-	10
8025PU2200190245	PU-2 200/190/24/5	5	-	-	180	-	-	10
8025PU2230220365	PU-2 230/220/36/5	5	-	-	-	10	-	10
8025PU2260250158	PU-2 260/250/15/8	8	240	-	-	-	-	10
8025PU2290280308	PU-2 290/280/30/8	8	-	-	240	15	-	10

## Blueprint

