

## Geared Trolley type 21

### Product information

Low-built block trolley for hanging e.g. chain blocks and wire hoists. The trolley can be supplied with a load of 0.5 tons up to 5 tons. The trolley has corner protection which prevents the trolley from detaching from the beam and ball bearing wheels. It is easily adjustable by the left- and right-handed carrier bracket and fits most brands of hoists.

**Marking:** WLL, name plate and CE.

**Finish:** Black painted.



Part Code	WLL ton	Beam width mm mm	Type	Min curve r m	B mm	C mm	Ø D mm	E mm	F mm	G mm	H mm	Ø J mm	Ø K mm	L mm	M mm	Ø O mm	P mm	R mm	Weight kg	Delivery time
502300051600430	0.5	50-160	21123A	1,25	212	20	70	88	20	56	35	32	19	264	130	100	24	104	14.3	10
502300052800430	0.5	161-280	21124A	1,25	A+57	20	70	88	20	56	35	32	19	264	130	100	24	104	15.5	10
502300101600430	1	50-160	21143A	1,25	212	20	70	88	20	51	40	32	24	264	130	100	24	104	14.3	10
502300102800430	1	161-280	22144A	1,25	A+57	20	70	88	20	51	40	32	24	264	130	100	24	104	15.5	10
502300201800430	2	64-180	21163A	1,80	248	24	100	120	24	63	51	40	32	335	165	100	31	118	25.3	10
502300203000430	2	181-300	21164A	1,80	A+76	24	100	120	24	63	51	40	32	335	165	100	31	118	27.4	10
502300301800430	3	74-180	21173A	2,20	262	28	114	137	30	78	57	46	35	380	180	165	37	130	38.2	10
502300303000430	3	181-300	21174A	2,20	A+89	28	114	137	30	78	57	46	35	380	180	165	37	130	41.2	10
502300501800430	5	82-180	21193A	2,50	270	34	140	166	32	92	64	56	42	437	215	205	41	132	56.7	10
502300503000430	5	181-300	21194A	2,50	A+97	34	140	166	32	92	64	56	42	437	215	205	41	132	60.4	10

# Blueprint

