



Horizontal Lifting Clamp THSK

Product information

Lifting clamp with adjustable extra large jaw opening for horizontal lifting, handling and transporting of stacks, packages and single steel plates. Terrier THSK lifting clamps must always be used in pairs (or multiple pairs). The adjustable jaw offers wide variety of openings available from 3 to 420 mm.

Features:

- Easy adjustable jaw opening
- Quick and easy placing and removing of the clamp
- Lightweight design for easy handling
- Tough quality heavy duty welded body

Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

Temperature range: - 40°C up to +100°C.

Standard: EN 13155

Note: The lifting clamps are suitable for lifting and transporting of steel plates with a maximum hardness of 37 HRC (345 HB, 1166 N/mm²). The lifting clamps must always be used in pairs (or multiple pairs).

Warning: Hardness level of the material surface may not exceed 37 Hrc (345 Hb, 1166 N/mm²)

| Part Code | Code | WLL ton | Jaw width mm | V mm | S mm | W mm | T mm | H mm | U mm | X mm | Y mm | Z mm | Weight kg | Delivery time |
|-----------------|--------------|---------|--------------|------|------|------|------|------|------|------|------|------|-----------|---------------|
| 502100151800700 | 1.5 THSK/180 | 1.5 | 3-180 | 201 | 135 | 15 | 30,5 | 18 | 289 | 90 | 20 | 60 | 9.5 | 10 |
| 502100153000700 | 1.5 THSK/300 | 1.5 | 3-300 | 201 | 135 | 15 | 30,5 | 18 | 409 | 90 | 20 | 60 | 11 | 10 |
| 502100301800700 | 3 THSK/180 | 3 | 3-180 | 241 | 165 | 20 | 30,5 | 18 | 296 | 105 | 20 | 69 | 13 | 10 |
| 502100303000700 | 3 THSK/300 | 3 | 3-300 | 241 | 165 | 20 | 30,5 | 18 | 416 | 105 | 20 | 69 | 15 | 10 |
| 502100451800700 | 4.5 THSK/180 | 4.5 | 3-180 | 241 | 165 | 20 | 30,5 | 18 | 296 | 105 | 20 | 69 | 13 | 10 |
| 502100454200700 | 4.5 THSK/420 | 4.5 | 3-420 | 241 | 165 | 20 | 30,5 | 18 | 536 | 105 | 20 | 69 | 17 | 10 |
| 502100601800700 | 6 THSK/180 | 6 | 3-180 | 256 | 160 | 25 | 30,5 | 18 | 304 | 120 | 20 | 75 | 18 | 10 |
| 502100604200700 | 6 THSK/420 | 6 | 3-420 | 256 | 160 | 25 | 30,5 | 18 | 544 | 120 | 20 | 75 | 24 | 10 |
| 502100901800700 | 9 THSK/180 | 9 | 3-180 | 256 | 160 | 25 | 30,5 | 18 | 304 | 120 | 20 | 75 | 18 | 10 |
| 502100904200700 | 9 THSK/420 | 9 | 3-420 | 256 | 160 | 25 | 30,5 | 18 | 544 | 120 | 20 | 75 | 24 | 10 |

Blueprint

