



Crane Scale Dynafor™ LLX2 - discontinued

Product information



The Dynafor™ LLX2 is a major innovation in industrial dynamometry, providing the highest degree of ergonomics, precision reliability, flexibility and endurance.

- The LLX2 sensor unit with its unique design measures the force; this is the systems body.
- The LLX2 mobile display processes and displays the data; this is the systems brain.

An extended range: The dynafor™ LLX2 comes in 7 capacities: 0.5 t, 1 t, 2 t, 3.2 t, 6.3 t and 10.0 t.

Resistant to shocks and weather: The sensor dynafor™ LLX2 can be used indoor and outdoor with its excellent shock and moisture resistance, complying with protection IP66.

High precision: The dynafor™ LLX2 ensures a precision of 0.1%: the market reference.

PC link: The connection kit option (PC/dynafor™ LLX2 with USB) allows advanced processing of the measurement data.

Trademark of the TRACTEL Group

Material: Steel, aluminium

Temperature range: -20°C up to +40°C.

Part Code	WLL ton	Type	Precision 0,1 % daN	Increment daN	Max. display daN	Radio range m	RF technology GHz	Weight kg	Delivery time
423500050070	0.5	LLX2 0.5	0,5	0,1	550	80	2.4	2.3	10
423500100070	1	LLX2 1	1,0	0,2	1	80	2.4	2.3	10
423500200070	2	LLX2 2	2,5	0,5	2.2	80	2.4	2.3	10
423500320070	3.2	LLX2 3.2	2,5	0,5	3.52	80	2.4	2.3	10
423500500070	5	LLX2 5	5,0	1,0	5.5	80	2,4	3.35	10
423500630070	6.3	LLX2 6.3	5,0	1,0	6.93	80	2.4	3.35	10
423501000070	10	LLX2 10	10	2,0	11	80	2.4	6.45	10