

Welded Master Link Assembly X-0082



Product information

Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.
At least 25% greater WLL than traditional Grade 8 products. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part Code	Code	WLL	EWL	Proof Load	For chain gr 10 Ø 2 leg	For chain gr 10 Ø 3-4 leg	WLL 0-45°	Used to single hook acc. to DIN 15401 No.	D	A	B	d	a	b	Weight	Delivery time
		ton		kN	mm	mm	ton		mm	mm	mm	mm	mm	mm	kg	
402100360440	ED-22	3.55	394	87	6,7,8	6	3,55	25	0.87	13.39	7.09	0.51	2.13	0.98	3.2	5
402100560440	ED-28	5.6	374	137	10	7,8	5,6	25	1.1	13.39	7.09	0.63	2.76	1.34	5.4	5
402100950440	ED-32	9.5	425	233	13	10	9,5	25	1.26	13.39	7.09	0.75	3.35	1.57	7.4	5
402101410440	ED-40	14.1	455	343	16	13	14,1	25	1.57	13.39	7.09	0.87	4.53	1.97	12.1	5
402102110440	ED-40	21.2	480	519	20	16	21,2	25	1.57	13.39	7.09	0.98	5.51	2.56	14.2	10

Blueprint

