



Master Link Grab 1 Assy X-A06

Product information

At least 25% greater WLL than traditional Grade 8 products.
Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Fully integrated shortening hooks and master link.
No reduction in WLL when shortening chain.
Speedy assembly.
Light weight system.
Cost effective compared to slings which use multiple components.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	WLL 45- 60° ton	WLL 0-45° ton	Can be used to single hook acc. To	Weight kg	Delivery time
402100290480	6	2.9	2,1	2,9	6	2.4	10
402100530480	8	5.3	3,8	5,3	10	4.6	5
402100840480	10	8.4	6,0	8,4	10	8.1	10
402101410480	13	14.1	10,1	14,1	12	15.8	10
402102100480	16	21	15,0	21,0	20	28.9	10
402103360480	20	33.6	24,0	33,6	32	44.9	10
402103990480	22	39.9	28,5	39,9	32	52.2	10

Blueprint

