



## Eye Self Locking Hook X-025

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-3

**Safety factor:** 4:1

**Grade:** 10

Part Code	Chain diameter mm	WLL ton	EWL mm	A mm	D mm	H mm	K mm	P mm	T mm	Weight kg	Delivery time
402300140720	6	1.4	110	21	10	19	110	28	15	0.5	5
402300250720	7-8	2.5	136	25	11	24	136	34	20	0.8	5
402300400720	10	4	167	32	13	30	167	44	26	1.5	5
402300670720	13	6.7	207	40	16	39	207	51	30	3	5
402301000720	16	10	252	50	21	49	252	60	36	5.8	5
402301600720	20	16	290	60	23	65	290	70	53	10	5
402301900720	22	19	319	70	24	63	319	80	49	12.5	5
402302650720	26	26.5	343	80	25	69	343	99	56	15	10

## Blueprint

