



Clevis Sling Hook X-043/S Grade 10

Product information

At least 25% greater WLL than traditional Grade 8 products.
 Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
 Tempering temperature minimum 400°C.
 Magnaflux crack detection is performed 100% on each batch.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-2

Safety factor: 4:1

Grade: 10

Part Code	WLL ton	EWL mm	For Grade 100 Chain mm	A mm	H mm	K mm	P1 mm	T mm	Weight kg	Delivery time
402300140700	1.4	79	6	7	18	79	23	15	0.3	10
402300250700	2.5	98	7, 8	9	22	98	27	18	0.6	5
402300400700	4	122	10	12	30	122	34	24	1.1	5
402300670700	6.7	147	13	15	37	147	44	30	2.3	5
402301000700	10	166	16	17	41	166	48	39	3.8	5
402301600700	16	207	20	24	64	207	57	48	8.7	10
402301900700	19	217	22	25	61	217	73	52	9.5	5

Blueprint

