



Round Sling self locking Hook X-028

Product information

At least 25% greater WLL than traditional Grade 8 products.
 Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
 Fatigue rated to 20,000 cycles at 1.5 times the WLL.
 Tempering temperature minimum 400°C.
 Magnaflux crack detection is performed 100% on each batch.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	For Grade 100 Chain mm	H mm	K mm	P mm	T mm	W mm	Weight kg	Delivery time
402300140780	6	1.4	6	19	138	29	15	38	0.6	5
402300250780	7-8	2.5	7, 8	24	169	34	20	40	1	5
402300400780	10	4	10	30	196	44	26	47	1.8	10
402300670780	13	6.7	13	39	253	52	30	53	3.9	10
402301000780	16	10	16	49	305	60	36	67	6.9	5
402301600780	20	16	20	62	328	90	48	80	12	10
402301900780	22	19	22	63	416	80	49	125	18.6	10

Blueprint

