



Eye Grab Hook X-079

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- No reduction in WLL when shortening chain.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

| Part Code | Chain diameter mm | WLL ton | EWL mm | A mm | B mm | D mm | F mm | K mm | L mm | P mm | Weight kg | Delivery time |
|--------------|----------------------|------------|-----------|---------|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 402300140760 | 5-6 | 1.4 | 76 | 8 | 18 | 9 | 24 | 76 | 99 | 12 | 0.24 | 5 |
| 402300250760 | 7-8 | 2.5 | 102 | 10 | 24 | 13 | 32 | 102 | 134 | 12 | 0.54 | 5 |
| 402300400760 | 10 | 4 | 125 | 12 | 31 | 14 | 40 | 125 | 163 | 15 | 1.03 | 5 |
| 402300670760 | 13 | 6.7 | 158 | 16 | 37 | 18 | 51 | 158 | 208 | 20 | 2.18 | 5 |
| 402301000760 | 16 | 10 | 202 | 19 | 48 | 24 | 64 | 202 | 264 | 21 | 4.39 | 5 |

Blueprint

