



Solid Wire Rope Thimble Crosby S-412

Product information

Fits pin for open wire rope socket, boom pendant clevis and wedge socket.

Features: Greater protection against wear and deformation of the wire rope eye giving longer service life.

Material: Cast Ductile Iron.

Marking: Manufacturer's symbol.

| Part Code | Diameter mm | Rope Ø range mm | A mm | B mm | C mm | D mm | D tolerance | E mm | F mm | G mm | H mm | J mm | K mm | L mm | Weight kg | Delivery time |
|--------------|-------------|-----------------|------|------|------|------|-------------|------|------|------|------|------|------|------|-----------|---------------|
| 123101600220 | 0 | 16 | 119 | 76 | 9.65 | 33.3 | +4% | 26.9 | 20.6 | 10.4 | 28.7 | 86 | 57 | 65 | 1 | 5 |
| 123101300220 | - | 13 | 71.5 | 44.5 | 6.35 | 26.9 | +5% | 19.1 | 14.2 | 7.1 | 22.4 | 54 | 41.4 | 39.6 | 0.28 | 10 |
| 123102000220 | - | 18-20 | 119 | 76 | 9.65 | 38.1 | +3% | 26.9 | 20.6 | 10.4 | 35.1 | 86 | 57 | 65 | 1.05 | 5 |
| 123102200220 | - | 22 | 154 | 97 | 12.7 | 44.5 | +3% | 35.1 | 26.9 | 13.5 | 41.4 | 114 | 82.5 | 87.5 | 2.47 | 10 |
| 123102600220 | - | 24-26 | 154 | 97 | 12.7 | 54 | +3% | 35.1 | 26.9 | 13.5 | 46 | 114 | 82.5 | 87.5 | 2.38 | 5 |
| 123103000220 | - | 28-30 | 184 | 116 | 16 | 60.5 | +2% | 44.5 | 33.3 | 16.8 | 52.5 | 137 | 98.5 | 103 | 4.21 | 5 |
| 123103500220 | - | 32-35 | 184 | 116 | 16 | 67 | +2% | 49.3 | 38.9 | 19.8 | 58.5 | 137 | 98.5 | 105 | 4.45 | 10 |

Blueprint

