



## Clevis Grab Hook X-042

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Testing according to DIN PAS 1061 and ASTM A952/A 952M.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Material:** Quenched and Tempered Alloy Steel

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Standard:** EN 1677-1

**Warning:** Not for use with Omega Link

**Safety factor:** 4:1

**Grade:** 10

| Part Code    | Chain diameter<br>mm | WLL<br>ton | EWL<br>mm | A<br>mm | F<br>mm | H<br>mm | K<br>mm | L<br>mm | P<br>mm | Weight<br>kg | Delivery time |
|--------------|----------------------|------------|-----------|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 402300140810 | 6                    | 1.4        | 47        | 7       | 25      | 18      | 47      | 79      | 8       | 0.2          | 10            |
| 402300250810 | 7-8                  | 2.5        | 54        | 10      | 30      | 22      | 54      | 93      | 10      | 0.4          | 10            |
| 402300400810 | 10                   | 4          | 77        | 11      | 41      | 29      | 77      | 128     | 13      | 0.8          | 10            |
| 402300670810 | 13                   | 6.7        | 99        | 15      | 52      | 38      | 99      | 165     | 17      | 1.6          | 5             |
| 402301000810 | 16                   | 10         | 114       | 18      | 57      | 45      | 114     | 195     | 21      | 2.7          | 5             |
| 402301600810 | 20                   | 16         | 130       | 22      | 73      | 52      | 130     | 222     | 23      | 4.8          | 5             |
| 402301900810 | 22                   | 19         | 139       | 24      | 70      | 56      | 139     | 247     | 26      | 6.4          | 10            |

## Blueprint

