

## Elevator rope 8x19S-IWRC

### Product information



**General:** Steel wire rope for use in elevator.

**Tolerance  $\varnothing$ :**  $\leq 10$  mm 0% - +6%,  $> 10$  mm 0% - +5%.

**Rope construction:** 8x19-IWRC.


**Marking:** According to standard

**Finish:** Ungalvanised

**Standard:** EN 12385-5

**Fill factor:** 0.59

Elevator



Part Code	Rope Diameter, mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay.	Min. Breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
106100804020219	8	1,570	Bright	sZ	37.9	31.1	SupplierStandard	27
106100904020219	9	1,570	Bright	sZ	48	38.1	SupplierStandard	34
106101004020219	10	1,570	Bright	sZ	58.5	46.6	SupplierStandard	41
106101104020219	11	1,570	Bright	sZ	69.7	55.6	SupplierStandard	49
106101204020219	12	1,570	Bright	sZ	83.6	66.4	SupplierStandard	59
106101304020219	13	1,570	Bright	sZ	100	79.5	SupplierStandard	70
106101404020219	14	1,570	Bright	sZ	116	91.8	SupplierStandard	81
106101504020219	15	1,570	Bright	sZ	131	104	SupplierStandard	92
106101604020219	16	1,570	Bright	sZ	148	118	SupplierStandard	105