



## Wide Mouth Shackle G-4263

### Product information

Bow shackles with safety bolt.

**Certification:** This product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate and/or EC Declaration of Conformity.

**Material:** Bow and pin alloy steel, quenched and tempered

**Marking:** CE-marked

**Temperature range:** -20°C up to +200°C

**Finish:** Hot dip galvanized

**Note:** This shackle can also be delivered with fixed nut (an extra AISI 316 securing bolt is drilled through both the nut and shackle pin. This securing bolt is fastened with two sets of Nord-Lock®)

**Safety factor:** 6:1

**Grade:** 8

Part Code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	Weight kg	Delivery time
420100481020	4.75	22	25	52	22	63	112	88	173	157	132	23	2.08	10
420100651020	6.5	25	28	59	25	75	135	105	204	183	155	25	3.14	10
420100851020	8.5	28	32	66	28	82	148	115	225	205	171	27	4.36	10
420100951020	9.5	32	35	72	32	90	162	126	248	224	190	30	5.95	10
420101201020	12	35	38	79	35	100	180	140	274	245	210	33	7.87	10
420101601020	16	38	42	88	38	106	216	159	319	248	235	19	12.5	10
420102501020	25	45	50	103	45	127	248	175	370	296	265	23	16.7	10
420103001020	30	50	57	118	50	146	273	207	411	332	307	26	25	10
420105501020	55	65	70	145	65	165	314	213	487	391	343	32	45	10
420107501020	75	83	83	164	83	184	330	254	537	460	420	39	70	10

# Blueprint

