



## Round Sling POWERTEX PRS r-PET

### Product information



POWERTEX Round slings PRS r-PET are made from high-strength **recycled** polyester (r-PET) yarn having a robust protective cover. Because it is made from r-PET yarn, this product **has a 75% CO2 reduction\*** compared to the standard PRS round sling.

Because of this sustainability enhancement, this product is approved to be part of Lifting Solution Group's [Aspire range™](#). In November 2023, this product won the prestigious LEEA Sustainable Award.

The PRS r-PET slings are color coded for quick and easy identification of the Working Load Limit (WLL).

- Safe – All POWERTEX PRS r-PET slings are made from high-strength recycled polyester and tested in accordance with EN 1492-2
- Durable protective cover
- Each sling carries a blue label giving the correct WLL for different load connection methods and angles
- Each sling is marked with a unique serial number for safe sling registration
- Serial number is expressed both in a numeric format as well as Barcode for quick registration and maintenance
- Year/Month calendar printed on the label where the next inspection date can be marked or punched
- Printing on the blue label is protected by an additional transparent plastic layer for long life
- All round slings carry a white label showing a pictogram with important user warning instructions
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each sling

**Chemical resistance:** Resistant to most acids, but not strong alkalizes.

**Stretch at working load:** 2-3%.

**Length tolerance:** Nominal length (EWL)  $\pm 2\%$ .

\*A 3rd party climate LCA with a cradle-to-gate perspective according to ISO14067 has shown that our r-PET round slings have 75% less CO2e emissions than our standard product. This means that our products are not only better for the environment but also make a positive contribution to reducing CO2 emissions.

**Material:** Polyester (PES), high tenacity multifilament made from r-PET (recycled PET).

**Marking:** According to standard, CE-marked, UKCA-marked, The slings are provided with a blue label and a white warning label with Aspire range information on the back side.

**Temperature range:** -40°C up to +100°C

**Standard:** EN 1492-2

**Note:** Currently available in WLL 1t up to 5t and lengths 1 to 6 meter. Other variants on request

**Warning:** According to EN 1492-1:2000+A1:2008: D.3.7: Slings should be protected from edges, friction and abrasion, whether from the

load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

**Safety factor:** 7:1

Part Code	WLL ton
340100100100330	1
340100200100330	2
340100300100330	3
340100500100330	5