



Inferno® Soft Sling

Product information

Inferno®: The Heat Resistant Soft Sling

The ultra-heat resistant Inferno® soft sling makes it possible to lift heavy payloads when working under extreme heat conditions. Even when the temperature rises to 200°C, the Inferno® soft sling will maintain strength!

Properties:

The Inferno® soft sling is made of 100% Aramid and available from 0,5m to 65m, with a WLL up to 100t. Inferno® cover can be manufactured in the color black for WLL up to a maximum of 2.5 tons, while those from 3 tons and above are yellow (the natural color of Aramid fiber).

Features:

- Maintains its strength up to 200°C(!)
- Easy to position
- Low D:d ratio
- Soft, lightweight, and easy to handle
- Improves workflow
- High abrasion resistance
- Environmentally friendly due to the long lifespan
- Creates safer lifting conditions

Sustainability:

The Inferno® heat-resistant soft sling jacket is repairable, making it a sustainable option. In case of damage to the jacket, it can be repaired, extending the lifespan of the sling and reducing waste.

Material: 100% Aramid

Marking: According to standard, CE-marked, UKCA-marked

Temperature range: to +200°C

Standard: EN 1492-2

except material

Note: kg/m = kg/EWL

Warning: Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

Safety factor: 7:1

Part Code	WLL ton
34050010XXX0110	1
34050020XXX0110	2
34050030XXX0110	3
34050050XXX0110	5
34050100XXX0110	10
34050200XXX0110	20
34050400XXX0110	40
34050500XXX0110	50