

## Polypropylene Fibre Rope 3-Strand.



### Product information

Fibre rope of polypropylene for all different kinds of applications like: tarpaulin- and towing-ropes, lifting slings, ropes for the fishing industry, cargo nets, rope ladders, and more. The structure of the fibre rope makes it non-sliding in knots and splices.

**Design:** Spliced fibre.

**Specific gravity:** 0,91 (floats).

**Melting point:** Approx. 165°C.

**Elongation at MBL:** Approx. 30%.

**Strength wet/dry:** 100%

**Shock Absorption:** Very Good

**Water Absorption:** None

**Abrasion Resistance:** Good

**Material:** Polypropylene, resistant to rot, most acids and alkalis. The fibre is UV-stabilized against sunlight.

**Marking:** According to standard

**Finish:** Blue.

**Standard:** EN ISO 1346

Part Code	Diameter mm	MBL	Length m	Circ. inches	Weight kg/220m	Delivery time
300300402200010	4	0.28	220	3	1.54	10
300300409990010	4	0.28	1,000	3	1.54	10
300300502200010	5	0.45	220	3 1/4	2.42	10
300300602200010	6	0.55	220	3 1/2	3.52	5
300300605000010	6	0.55	500	3 1/2	3.52	10
300300802200010	8	0.96	220	3 3/4	6.38	10

300300803110010	8	0.96	311	3 3/4	6.38	10
300301002080010	10	1.43	208	4	9.9	10
300301002200010	10	1.43	220	4	9.9	10
300301200500010	12	2.03	50	4 1/2	14.3	10
300301202200010	12	2.03	220	4 1/2	14.3	10
300301400300010	14	2.79	30	5	19.58	10
300301402200010	14	2.79	220	5	19.58	10
300301600300010	16	3.5	30	5 1/2	25.52	10
300301602200010	16	3.5	220	5 1/2	25.52	10
300301802200010	18	4.45	220	6	32.12	10
300302002200010	20	5.37	220	3	39.82	10
300302202200010	22	6.5	220	3 1/4	48.18	10
300302402200010	24	7.6	220	3	57.2	10
300302602200010	26	8.45	220	3 1/4	67.32	10
300302802200010	28	10.1	220	3 1/2	77.88	10
300303202200010	32	12.8	220	4	101.86	10
300303602200010	36	16.1	220	4 1/2	128.92	10