



## TEC12

### Product information

**Typical application:** Mooring, towing and anchor

**Specific Gravity:** 0.94 (Float)

**Melting Point:** 165°C

**Water Absorption:** None

**Ultra-violet Light Resistance:** Good

**Abrasion Resistance:** Good

**Rope construction:** 12-strand (12x1)

**Material:** High tenacity polyolefin fiber

**Finish:** Blue/White

| <b>Part Code</b> | <b>Diameter<br/>mm</b> | <b>MBL</b> | <b>Length<br/>m</b> | <b>OMkr tum</b> | <b>Rope ends</b> | <b>Weight<br/>kg/220m</b> | <b>Delivery time</b> |
|------------------|------------------------|------------|---------------------|-----------------|------------------|---------------------------|----------------------|
| 301203602200071  | 36                     | 29.6       | 220                 | 4,5             | Eye in both ends | 141.02                    | 10                   |
| 301204002200071  | 40                     | 36.3       | 220                 | 5               | Eye in both ends | 174.02                    | 10                   |
| 301204402200071  | 44                     | 43.5       | 220                 | 5,5             | Eye in both ends | 214.94                    | 10                   |
| 301204802200071  | 48                     | 50.9       | 220                 | 6               | Eye in both ends | 251.9                     | 10                   |
| 301205202200071  | 52                     | 58.8       | 220                 | 6,5             | Eye in both ends | 294.8                     | 10                   |
| 301205602200071  | 56                     | 67.3       | 220                 | 7               | Eye in both ends | 343.2                     | 10                   |
| 301206002200071  | 60                     | 77         | 220                 | 7,5             | Eye in both ends | 393.8                     | 10                   |
| 301206402200071  | 64                     | 86.6       | 220                 | 8               | Eye in both ends | 448.8                     | 10                   |
| 301206802200071  | 68                     | 98.4       | 220                 | 8,5             | Eye in both ends | 506                       | 10                   |
| 301207202200071  | 72                     | 109.4      | 220                 | 9               | Eye in both ends | 567.6                     | 10                   |
| 301208002200071  | 80                     | 134.1      | 220                 | 10              | Eye in both ends | 701.8                     | 10                   |
| 301208802200071  | 88                     | 161.3      | 220                 | 11              | Eye in both ends | 849.2                     | 10                   |
| 301209602200071  | 96                     | 190.3      | 220                 | 12              | Eye in both ends | 569.8                     | 10                   |

## Blueprint

