

D Shackle 316 Stainless



Product information



Design: Stainless steel D shackle, with pin. Good for lifting applications where a high level of corrosion resistance is required. Typical applications: Water utility installations & other corrosive facilities, Pump chains and pump lifting, Chemical installations - Chlorine plants etc, General lifting in off-shore applications, General lifting and tethering in leisure marine applications, General lifting purposes.

Proof load: 2x WLL

Material: Stainless Steel EN10088 1.4404 (Marine Grade 316L)

Marking: According to standard, CE-marked, WLL, Supplier

Finish: Polished

Standard: EN 10204

Safety factor: : 6:1

Part Code	WLL ton	EWL mm	B mm	J mm	L mm	P mm	Weight kg	Delivery time
420100010120	0.13	16	4	8	16	4	0.07	5
420100020120	0.2	20	5	10	20	5	0.013	10
420100030120	0.325	25	6	13	25	6	0.024	5
420100050120	0.5	32	8	16	32	8	0.053	10
420100080120	0.8	38	9,5	19	38	9,5	0.097	10
420100100120	1	44	11	22	44	11	0.152	10
420100130120	1.25	52	12,7	26	52	12,7	0.237	10
420100170120	1.66	58	14,3	29	58	16	0.45	10
420100230120	2.33	64	16	32	64	19	0.585	5
420100350120	3.5	76	19	38	76	22,2	1	10
420100450120	4.5	88	22,2	44	88	25,4	1.9	10
420100550120	5.5	102	25,4	51	102	28,6	2.9	10
420100650120	6.5	114	28,6	57	114	31,8	3.1	10
420100750120	7.5	128	31,8	64	128	34,9	4.35	10
420100900120	9	140	34,9	70	140	38	5.3	10

Blueprint

