

Bow Shackle 316 Stainless

Product information



Design: Stainless steel bow shackle, with pin. Good for lifting applications where a high level of corrosion resistance is required. Typical applications: Water utility installations & other corrosive facilities, Pump chains and pump lifting, Chemical installations - Chlorine plants etc, General lifting in off-shore applications, General lifting and tethering in leisure marine applications, General lifting purposes.

Proof load: 2x WLL

Material: Stainless Steel EN10088 1.4404 (Marine Grade 316L)

Marking: CE-marked, WLL, Supplier,

Finish: Polished

Safety factor: 6:1



Part Code	WLL ton	EWL mm	B mm	J mm	L mm	P mm	W mm	Weight kg	Delivery time
420100010130	0.13	16	4	8	16	4	12	0.009	10
420100020130	0.2	22	5	10	22	5	16	0.014	10
420100030130	0.26	28	6	13	28	6	19	0.028	5
420100040130	0.4	35	8	16	35	8	25	0.059	5
420100060130	0.63	38	9.5	19	38	9.5	28	0.06	5
420100080130	0.8	46	11	22	46	11	33	0.161	10
420100100130	1	52	12.7	26	52	12.7	38	0.27	5
420100130130	1.33	60	14.3	29	60	16	43	0.5	10
420100200130	2	68	16	32	68	19	50	0.63	10
420100280130	2.75	76	19	38	76	22.2	57	1.05	10
420100380130	3.75	88	22.2	44	88	25.4	66	1.995	10
420100450130	4.5	102	25.4	51	102	28.6	76	3.045	10
420100550130	5.5	114	28.6	57	114	31.8	86	3.255	10
420100650130	6.5	128	31.8	64	128	34.9	95	4.568	10
420100750130	7.5	140	34.9	70	140	38	105	5.565	10

Blueprint

