

SS 6x19-FC

Product information



Typical applications: Cranes, hoist blocks, lifts, wire rope slings.

Material: AISI 316.

Marking: According to standard


Standard: EN 12385-4

Fill factor: 0.45

Slings



Overhead cranes



| Part Code | Rope Diameter, mm | Tensile strength N/mm ² | Finish | Rope lay. | Min. Breaking force kN | Steel area mm ² | Lubrication | Weight kg/100m |
|-----------------|----------------------|---------------------------------------|-----------|-----------|---------------------------|-------------------------------|-------------|-------------------|
| 108100304620128 | 3 | 1,570 | Stainless | sZ | 4.34 | 3.21 | No-Lube | 3.1 |
| 108100404620128 | 4 | 1,570 | Stainless | sZ | 7.71 | 5.71 | No-Lube | 5.5 |
| 108100504620128 | 5 | 1,570 | Stainless | sZ | 12 | 8.93 | No-Lube | 8.7 |
| 108100604620128 | 6 | 1,570 | Stainless | sZ | 17.4 | 12.9 | No-Lube | 13 |
| 108100704620128 | 7 | 1,570 | Stainless | sZ | 23.6 | 17.5 | No-Lube | 17 |
| 108100804620128 | 8 | 1,570 | Stainless | sZ | 30.8 | 22.8 | No-Lube | 22 |
| 108100904620128 | 9 | 1,570 | Stainless | sZ | 39 | 28.9 | No-Lube | 28 |
| 108101004620128 | 10 | 1,570 | Stainless | sZ | 48.2 | 35.7 | No-Lube | 35 |
| 108101204620128 | 12 | 1,570 | Stainless | sZ | 69.4 | 51.4 | No-Lube | 50 |