

## Steel Wire Rope 6x19-WSC stainless

### Product information



Steel wire rope 6x19 WSC in stainless steel is a good choice for basic lifting applications in environments where corrosion resistance is important. It is equipped with a Wire Strand Core (WSC) which gives the rope a good strength and a reasonable balance between fatigue and wear resistance. Can be used for applications where the rope runs over sheaves or is spooled on a drum.

**Rope construction:** 6x19M-WSC

**Material:** AISI 316

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C

**Standard:** EN 12385-4

*except material*

**Fill factor:** 0,53

**RCN:** 04


Winch rope



Stay rope



Overhead cranes



Agriculture and livestock



Slings



Part Code	Rope Diameter, mm	Tensile strength N/mm <sup>2</sup>	Steel area mm <sup>2</sup>	Min. Breaking force kN.	Finish	Weight kg/100m	Delivery time
108100204620138	2	1,570	-	-	Stainless	-	-
108100304620138	3	1,570	-	-	Stainless	-	-
108100404620138	4	1,570	-	-	Stainless	-	-
108100504620138	5	1,570	-	-	Stainless	-	-
108100604620138	6	1,570	-	-	Stainless	-	-
108100704620138	7	1,570	-	-	Stainless	-	-
108100804620138	8	1,570	-	-	Stainless	-	-
108100904620138	9	1,570	-	-	Stainless	-	-
108101004620138	10	1,570	-	-	Stainless	-	-
108101104620138	11	1,570	-	-	Stainless	-	-
108101204620138	12	1,570	-	-	Stainless	-	-
108101304620138	13	1,570	-	-	Stainless	-	-
108101404620138	14	1,570	-	-	Stainless	-	-
108101504620138	15	1,570	-	-	Stainless	-	-
108101604620138	16	1,570	-	-	Stainless	-	-
108101804620138	18	1,570	-	-	Stainless	-	-
108102004620138	20	1,570	-	-	Stainless	-	-