

Rigging Screw Stainless

Product information



Stainless steel rigging screw in design, fork/fork. Also available with other end fittings on request.

The larger size rigging screws from M20 and up are designed with a rounded fork head and are available with stainless steel with bronze threaded inserts for smooth adjustment. Delivered complete with locking nuts.

Material: Stainless steel AISI 316.

Marking: Thread and/or wire size and marking for left and right threaded side.

Temperature range: -50°C to +100°C and briefly up to +200°C

Finish: Polished.

Note: On request the rigging screws can be provided with thread stop

Warning: The turnbuckles are normally not intended for lifting. If they are to be used for lifting every individual turnbuckle shall be proof loaded, this is made on request. The turnbuckles are not allowed to be adjusted in length under load. When they are used for lifting It is strongly recommended to lubricate threads first, before tensioning.

Part Code	Breaking Load ton	Length mm	Pin diameter mm	Thread	G mm	A mm	B mm	L1 mm	L2 mm	Weight kg/100pc	Delivery time
492118000260	0.8	126-180	5	M5	M5	7,5	12	180	126	5.1	10
492120000260	1	138-200	5	M6	M6	7,5	12	200	138	9	5
492120200260	1.2	145-213	6	M6	M6	9,5	13	213	145	14	10
492123400260	1.6	170-251	6	M8	M8	9,5	13	251	170	14	5
492124000260	2.2	178-258	8	M8	M8	11	15	258	178	15	10
492127200260	3.2	188-272	8	M10	M10	11	15	272	188	24	5
492128000260	3.5	204-286	9.5	M10	M10	12	19	286	204	26	10
492135000260	5.1	251-359	12	M12	M12	14	25	359	251	52.5	5
492138700260	6.7	280-400	12	M14	M14	14	25	400	280	63.5	10
492137000260	5.1	269-375	14	M12	M12	18	32	375	269	72.2	10
492140500260	6.9	295-413	14	M14	M14	18	32	413	295	84.5	5
492148000260	9.4	320-480	14	M16	M16	18	32	480	320	100	10
492147200260	9.4	312-472	14	M16	M16	22	30	472	312	100	10
492144600260	9.4	313-446	16	M16	M16	18	33	446	313	100	5
492155000260	14	390-550	19	M20	M20	24	48	550	390	197	10
492154600260	14	389-559	19	M20	M20	30	47	559	389	197	10
492165300260	18.2	472-653	22	M22	M22	30	57	653	472	448	10
492176900260	21	539-769	25	M24	M24	30	62	769	539	638	10
492182500260	23	590-825	28	M27	M27	32	68	825	590	881	10
492190700260	28	647-907	32	M30	M30	35	76	907	647	1,060	10
492199000260	41	715-990	35	M36	M36	40	86	990	715	1,657	10

Blueprint

