



Steel Wire Rope 1x7

Product information



S

Z

A

Rope construction: 1x7

Marking: According to standard

Standard: SS 424 08 06

Fill factor: 0.78

Stay rope



| Part Code | Rope Diameter, mm | Tensile strength N/mm ² | Finish | Rope lay. | Min. Breaking force kN | Steel area mm ² | Lubrication | Weight kg/100m |
|-----------------|-------------------|------------------------------------|------------------|-----------|------------------------|----------------------------|-------------|----------------|
| 100100641520020 | 6.4 | 1,370/1,420 | Heavy galvanized | S | 32 | 25 | Dry | 19 |
| 100100642520020 | 6.4 | 1,370/1,420 | Heavy galvanized | Z | 32 | 25 | Dry | 19 |
| 100100731520020 | 7.3 | 1,370/1,420 | Heavy galvanized | S | 43 | 33 | Dry | 26 |
| 100100732520020 | 7.3 | 1,370/1,420 | Heavy galvanized | Z | 43 | 33 | Dry | 26 |
| 100100921520020 | 9.2 | 1,370/1,420 | Heavy galvanized | S | 68 | 52 | Dry | 41 |
| 100100922520020 | 9.2 | 1,370/1,420 | Heavy galvanized | Z | 68 | 52 | Dry | 41 |
| 100101061520020 | 10.6 | 1,370/1,420 | Heavy galvanized | S | 89 | 68 | Dry | 54 |
| 100101062520020 | 10.6 | 1,370/1,420 | Heavy galvanized | Z | 89 | 68 | Dry | 54 |
| 100101211520020 | 12.1 | 1,370/1,420 | Heavy galvanized | S | 116 | 89 | Dry | 70 |
| 100101212520020 | 12.1 | 1,370/1,420 | Heavy galvanized | Z | 116 | 89 | Dry | 70 |