



Lifters flexible Coupling Starcon

Product information

The Starcon Lifting Eye is a special steel component made for concrete casting. The spherical claw grips on to the head below the Starcon head anchor. The Starcon lifting eye has been tensile tested with 2 times of the safe load. Unique certificates are made for each delivery.

The Starcon product is designed according to EN13155-2009 and follows the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Material: Steel

Marking: CE-marked, UKCA-marked, Batch code, Load group, WLL, Starcon

Finish: Electro galvanized

Safety factor: 4:1

| Part Code | Load grp. t | b mm | d mm | h mm | L mm | Weight | Delivery time |
|--------------|-------------|------|------|------|------|--------|---------------|
| 650230013001 | 1-1.3 | 50 | 34 | 110 | 182 | 0.7 | 10 |
| 650230025001 | 1.5-2.5 | 60 | 42 | 120 | 210 | 1.28 | 10 |
| 650230050001 | 3-5.0 | 60 | 55 | 120 | 237 | 2.73 | 10 |
| 650230100001 | 6-10.0 | 100 | 74 | 200 | 340 | 7.05 | 10 |
| 650230200001 | 12-20.0 | 120 | 110 | 250 | 484 | 17 | 10 |

Blueprint

