



Hand spurgear Winch TIREX

Product information

Hand spurgear winch in compact design available in 150 and 300 kg, standard model with zinc-plated steel mounting plate.

Suitable for moderate use both indoor and outdoor.

Applications:

- Lifting of doors
- Opening of hatches
- Moving a boat
- Scenery handling
- Lifting equipment

Technical properties:

- Chassis made of an aluminum frame.
- Composite drum.
- Planetary reducer
- Mounting plate in galvanised steel
- Flat mounted.
- 4 fixation points.
- Removable crank.
- Free spooling drum, only when not in load.
- Automatic brake in composite material.
- Failsafe system for correct rope winding direction (patented).

Options: Galvanised Wire rope with hook or Fibre rope with hook

Material: Aluminum chassi / Zink plated mounting plate

Marking: According to standard, CE-marked

Temperature range: -10°C to +50°C

Standard: EN 13157

| Part Code | WLL ton | Rope Ø mm | Weight without wire rope kg | Capacity 1st layer kg | Number of layers | Lift per crank revolution mm | Max. crank effort kg | Max. drum capacity m | Weight kg | Delivery time |
|-----------------|---------|-----------|-----------------------------|-----------------------|------------------|------------------------------|----------------------|----------------------|-----------|---------------|
| 501300250000130 | 0.15 | 4 | 3.7 | 250 | 6 | 40 | 8 | 24 | 3.7 | 10 |
| 501300040000130 | 0.3 | 5 | 3.7 | 400 | 3 | 41 | 14 | 8.5 | 3.7 | 10 |

Blueprint

