

Cablegrip SK

Product information



General: Splice sock designed for splicing cable, synthetic rope, steel wire rope and hose. Consists of two DE socks that are assembled in the middle with a ferrule. Can be used for change of non-rotating crane ropes. Two DE socks assembled with swivel should be used when replacing a6 - and 8-wired steel wire rope so that no torque will be transferred onto the new wire rope.

Rope construction: : Braided of double wires.

Material: : Steel wire - galvanized.

Warning: Margin of safety is applied to all specified breaking loads. Additional safety factors, depending on area of use should be applied. CERTEX recommends a safety factor of 3:1 for horizontal pulls and 5:1 for overhead pulling. The breaking load varies with the material, shape, and also the diameter of the product.

Part Code	Rope Ø range mm	MBL	Length Eye	Length Net	Weight kg	Delivery time
140601200250	8-12	0.885	45	800	0.4	10
140601500250	12.5-15	1.41	60	1,100	0.65	10
140601900250	15.5-19	1.76	75	1,200	0.8	10
140602500250	19-25	2.1	85	1,200	1.2	10
140603800250	25-38	3.03	120	1,200	1.5	10
140605000250	38-50	4.39	155	1,200	1.75	10
140606300250	50.5-63	5.85	190	1,200	2.1	10

Blueprint

E - Enkel Ogel

