

Cablegrip ASK

Product information



General: Openi sock with a pressed-in eye for wire rope and and cable drawing or tubing fuse. The sock can be placed anywhere along the cable, rope or hose and then "snapped together". The eyes can be ordered with a thimble.

Rope construction: : Braided double ropes.

Material: : Steel wire - galvanized.

Warning: Margin of safety is applied to all specified breaking loads. Additional safety factors, depending on area of use should be applied. CERTEX recommends a safety factor of 3:1 for horizontal pulls and 5:1 for overhead pulling. The breaking load varies with the material, shape, and also the diameter of the product.

| Part Code | Diameter mm | Rope Ø range mm | MBL | Length Eye | Length Net | Weight kg | Delivery time |
|--------------|-------------|-----------------|-------|------------|------------|-----------|---------------|
| 140601500260 | 4 | 12-15 | 0.35 | 250 | 155 | 0.08 | 10 |
| 140601900260 | 4 | 15.5-19 | 0.435 | 250 | 155 | 0.08 | 10 |
| 140602500260 | 5 | 19-25 | 0.615 | 300 | 170 | 0.14 | 10 |
| 140603800260 | 6 | 25-38 | 1.17 | 300 | 170 | 0.25 | 10 |
| 140605000260 | 6 | 38-50 | 1.68 | 350 | 230 | 0.31 | 10 |

Blueprint

S - Sidemounted Ogle

