

Steel Plate Lifter

Product information

CERTEX

General: The lifting equipment is designed for horizontal lifting of one or more plates of the same width. The equipment consists of two fork lifters and a 4-leg chain sling. Always delivered complete.

Design: Cut reinforced plate forks together with weld assembled pipes gives optimal dimensioning and low weight. The geometry is adjusted to prevent the forks tilting from the plate as long as the minimum lift height is followed according to the table.

Proof: Batch proof 1,5 x WLL.

Material: Plate and pipe of high-strength structural steel

Marking: CE-marked, Badge with Type, WLL, maximum plate width

Finish: Yellow painted

Note: Please be aware that the H measurement represents the minimum required lifting height.

Warning: We recommend other lifting equipment for thin plates that can bend during the lift.



Part Code	Code	WLL ton	Hole diameter mm	Plate width m	Chain Ø mm	A mm	C mm	E mm	H mm	L mm	M mm	Weight kg	Delivery time
504100100100010	PPL-1	1		1	6	80	24	25	1,300	150	1,000	11	10
504100100150010	PPL-1	1		1.5	6	80	24	25	1,700	150	1,000	11	10
504100100200010	PPL-1	1		2	6	80	24	25	2,200	150	1,000	11	10
504100200100010	PPL-2	2		1	7	80	31	25	1,300	175	1,000	16	10
504100200150010	PPL-2	2		1.5	7	80	31	25	1,700	175	1,000	16	10
504100200200010	PPL-2	2		2	7	80	31	25	2,200	175	1,000	16	10
504100300100010	PPL-3	3		1	7	90	36	35	1,500	200	1,000	25	10
504100300150010	PPL-3	3		1.5	7	90	36	35	1,800	200	1,000	25	10
504100300200010	PPL-3	3		2	7	90	36	35	2,300	200	1,000	25	10
504100400100010	PPL-4	4		1	8	90	36	40	1,500	200	1,000	29	10
504100400150010	PPL-4	4		1.5	8	90	36	40	1,800	200	1,000	29	10
504100400200010	PPL-4	4		2	8	90	36	40	2,300	200	1,000	29	10
504100500100010	PPL-5	5		1	10	90	45	40	1,500	200	1,000	40	10
504100500150010	PPL-5	5		1.5	10	90	45	40	1,800	200	1,000	40	10
504100500200010	PPL-5	5		2	10	90	45	40	2,300	200	1,000	40	10
504100800100010	PPL-8	8		1	10	90	45	50	1,500	200	1,250	43	10
504100800150010	PPL-8	8		1.5	10	90	45	50	1,800	200	1,250	43	10
504100800200010	PPL-8	8		2	10	90	45	50	2,300	200	1,250	43	10
504101000100010	PPL-10	10		1	13	150	45	65	1,500	200	1,250	70	10
504101000150010	PPL-10	10		1.5	13	150	45	65	1,800	200	1,250	70	10
504101000200010	PPL-10	10		2	13	150	45	65	2,300	200	1,250	70	10

Blueprint

