



Beam Clamp IPTKU

Product information



General:

The IPTKU series beam clamp has an improved hinged hoisting eye that increases the loading angles and an optional new "Double Locking Device"

Features:

- Available in capacities of 2 thru 10 metric tons.
- Wide variety of jaw openings available: 75 to 460 mm".
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.

Material: Alloy steel.

Marking: According to standard, CE-marked

Standard: EN 13155

Part Code	WLL ton	Jaw width mm	I P Model.	Jaw A	C mm	D mm	E mm	H mm	J mm	K mm	Weight kg	Delivery time
502300201900020	2	75-190	2-IPTKU	75-190	A + 100	121	76	22	99	19	5.7	10
502300301900020	3	75-190	3-IPTKU	75-190	A + 100	121	89	22	122	22	6.4	10
502300402800020	4	120-180	4-IPTKU	120-180	A + 150	140	89	40	122	22	12.1	10
502300503500020	5	120-350	5-IPTKU	120-350	A + 175	140	89	40	122	22	14.5	10
502301004600020	10	200-460	10-IPTKU	200-460	A + 300	200	105	60	152	26	41	10

Blueprint

