

Vertical Lifting Clamp IPU10/H

Product information

General:

The IP10H vertical lifting clamps are used for the lifting, turning, moving or vertical transfer of **very hard** (up to 472HV10 (450 HB) sheet, plates, or fabrications, from horizontal to vertical and down to horizontal (180°) as needed. The hinged hoisting eye (a.k.a. universal eye) allows for the clamp to place and lift the load from any direction, or with a multiple leg sling without side-loading the clamp. Available in a variety of models:

- IPU10 Standard clamp for materials with a surface hardness to 363HV10 (345 HB).
- IPU10J Larger jaw opening.
- IPU10S For use with Stainless Steel material.
- IPU10H For use with materials with a surface hardness to 472HV10 (450 HB).

Features:

- Available in capacities of 0.5 thru 6 metric tons
- Higher Working Load Limits are available upon request.
- Wide variety of jaw openings available: 0 to 50 mm.
- · Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual and test certificate included with each clamp.
- Full 180° turning range for material transfer, turning or moving.
- · Lock open, lock closed ability with latch for pretension on material and then release of material.
- · Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

Marking: Logo, WLL, jaw capacity, serial number, proof load test date and CE-marking.

Note: Min. load is 10% of WLL.

Part Code	WLL ton	Jaw width mm	Model	Weight kg	Delivery time
502100050160330	0.5	0-16	0.5-IPU10H	1.9	10
502100100350330	1	0-35	1-IPU10H	7.6	10
502100200400330	2	0-40	2-IPU10H	14.8	10
502100300400330	3	0-40	3 -IPU10H	16	10
502100450500330	4.5	0-50	4,5-IPU10H	24	10
502100600500330	6	0-50	6-IPU10H	29.5	10

Blueprint



