



Vertical Lifting Clamp IPU10

Product information



The IPU10 vertical lifting clamp is used for lifting, turning, moving or vertical transfer of sheet, plates, or fabrications from horizontal to vertical and down to horizontal (180°) as needed. The hinged hoisting eye (a.k.a. universal eye) allows for the clamp to place and lift the load from any direction, or with a multiple leg sling without side-loading the clamp. Available in a variety of models:

- IPU10 - Standard clamp for materials with a surface hardness to 363HV10 (345 HB).
- IPU10J - Larger jaw opening.
- IPU10S - For use with Stainless Steel material.
- IPU10H - For use with materials with a surface hardness to 472HV10 (450 HB).

Features:

- Available in capacities of 0.5 thru 30 metric tons
- Higher Working Load Limits are available upon request.
- Wide variety of jaw openings available: 0 to 155 mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual and test certificate included with each clamp.
- Full 180° turning range for material transfer, turning or moving.
- Lock open, lock closed ability with latch for pretension on material and then release of material.
- For use with materials with surface hardness to 279HV10, only 5% min WLL is needed.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

Material: Alloy steel.

Marking: According to standard, CE-marked

Standard: EN 13155

Warning: A minimum load of 10% of the WLL is required. Except for WLL 500 KG which requires a minimum load of 5% of WLL.

Safety factor: 4:1

| Part Code | Code | WLL ton | Jaw width mm | Model | B mm | C mm | D mm | E mm | F mm | G mm | H mm | J mm | K mm | Weight kg | Delivery time |
|-----------------|----------|---------|--------------|------------|------|------|------|------|------|------|------|------|------|-----------|---------------|
| 502100050160350 | 0.5IPU10 | 0.5 | 0-16 | 0.5-IPU10 | 44 | 130 | 216 | 40 | 115 | 42 | 28 | - | 11 | 1.9 | 10 |
| 502100100200350 | - | 1 | 0-20 | 1-IPU10 | 45 | 139 | 225 | 40 | 127 | 42 | 38 | - | 11 | 2.4 | 10 |
| 502100200350350 | - | 2 | 0-35 | 2-IPU10 | 78 | 201 | 368 | 70 | 188 | 64 | 55 | - | 16 | 8.5 | 10 |
| 502100300400350 | - | 3 | 0-40 | 3-IPU10 | 100 | 253 | 436 | 75 | 222 | 78 | 60 | - | 20 | 14.8 | 10 |
| 502100450400350 | - | 4.5 | 0-40 | 4.5-IP10 | - | - | - | - | - | - | - | - | - | 16 | 10 |
| 502100600500350 | - | 6 | 0-50 | 6-IPU10 | 126 | 302 | 525 | 80 | 292 | 84 | 95 | 44 | 20 | 24 | 10 |
| 502100900500350 | - | 9 | 0-50 | 9-IPU10 | 126 | 325 | 552 | 80 | 310 | 94 | 104 | 44 | 20 | 29.5 | 10 |
| 502101200540350 | - | 12 | 0-54 | 12-IPU10 | 160 | 392 | 616 | 80 | 433 | 121 | 137 | 41 | 25 | 57 | 10 |
| 502101600640350 | - | 16 | 5-64 | 16-IPU10 | 180 | 463 | 736 | 88 | 492 | 121 | 153 | 45 | 25 | 79 | 10 |
| 502102250800350 | - | 22.5 | 5-80 | 22.5-IPU10 | 222 | 554 | 863 | 110 | 565 | 139 | 186 | 49 | 25 | 126 | 10 |
| 502103000800350 | - | 30 | 5-80 | 30-IPU10 | 222 | 554 | 868 | 110 | 580 | 153 | 186 | 54 | 30 | 141 | 10 |

Blueprint

