



## Swivel Jaw / Jaw Crosby S2

### Product information

**Design:** Swivel with jaws equipped with tapered roller thrust bearing.

**Features:**

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- All jaws complete with bolts, nuts and cotter pins.
- Other types and capacities up to 1250 t available on demand.

**Marking:** CE-marked

**Note:** Always check before use if your steel wire rope is suitable for use with a swivel.

**Warning:** Not to be used on demolition- (wrecking-) balls!

**Safety factor:** 5:1

| Part Code    | Rope Ø range mm | WLL ton | Swivel No | B mm | G mm | H mm | J mm | K mm | N mm | O mm | Weight kg | Delivery time |
|--------------|-----------------|---------|-----------|------|------|------|------|------|------|------|-----------|---------------|
| 422500300080 | 13              | 3       | 3-S-2     | 236  | 70   | 19.1 | 22.4 | 41.1 | 33.3 | 25.4 | 4.37      | 10            |
| 422500500080 | 16              | 5       | 5-S-2     | 262  | 76   | 22.4 | 25.4 | 57   | 41.1 | 28.4 | 6.21      | 10            |
| 422500850080 | 19              | 8.5     | 8-S-2     | 321  | 102  | 25.4 | 39.5 | 71.5 | 54   | 35.1 | 11.9      | 10            |
| 422501000080 | 22              | 10      | 10-S-2    | 426  | 114  | 38.1 | 44.5 | 86   | 89   | 44.5 | 20.8      | 10            |
| 422501500080 | 26              | 15      | 15-S-2    | 435  | 127  | 38.1 | 44.5 | 86   | 89   | 44.5 | 28.5      | 10            |
| 422502500080 |                 | 25      | 25-S-2    | 527  | 152  | 51   | 51   | 117  | 93.5 | 60.5 | 64        | 10            |
| 422503500080 |                 | 35      | 35-S-2    | 527  | 165  | 51   | 51   | 117  | 93.5 | 60.5 | 70        | 10            |
| 422504500080 |                 | 45      | 45-S-2    | 641  | 178  | 57   | 63.5 | 127  | 102  | 76   | 107       | 10            |

## Blueprint

