



Chain Coupler Crosby S-1325A

Product information

Features:

- Locking system that provides for simple assembly and disassembly – no special tools required.
- Designed to connect Grade 100 chain fittings produced with “Engineered Flat” to Grade 100 chain.
- Suitable for use with Grade 100 and Grade 80 chain.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.

Material: Forged Alloy Steel - Quenched and Tempered.

Marking: Chain size, code and grade.

Finish: Painted.

Safety factor: 4:1

Grade: 10

Part Code	Code	Chain diameter mm	WLL ton	C mm	F mm	G mm	Weight kg	Delivery time
402200150010	S-1325A-6-10	6	1.5	26.2	19.3	44.7	0.11	10
402200200010	S-1325A-7-10	7	2	35.8	22.4	59	0.23	5
402200250010	S-1325A-8-10	8	2.5	35.6	22.4	59	0.23	5
402200400010	S-1325A-10-10	10	4	46.7	30	69	0.34	5
402200680010	S-1325A-13-10	13	6.8	55.6	38.1	94.5	0.75	10
402201030010	S-1325A-16-10	16	10.3	71.4	49.8	112	0.86	10

Blueprint

