

Rope Pear Socket Nemag



Product information

The Nemag Rope Pear Socket is designed to, in combination with the Nemag Quick Release Link, smoothly pass over cable sheaves. The life span of the Nemag Rope Pear Socket generally surpasses that of the steel wire rope. The Rope Pear socket can be fitted by casting with a 2-component casting mass without the need for outside assistance, and ensures a strong connection. Nemag Rope Pear Sockets are suited to any type of steel wire rope.

Material: High grade casted steel.

Marking: Manufacturers logo, size and batch number.

Warning: The specified capacities shown are for grab operation. For other applications use safety factor 5:1

Safety factor: 5:1

Part Code	Code	Rope Ø range mm	WLL ton	MBL	Weight kg	Delivery time
122101100120	RP-1	10-11	1.5	10	0.4	10
122101300120	RP-2	12-13	2	14	0.4	5
122101500120	RP-3	14-15	2.5	17.5	0.6	10
122101700120	RP-4	16-17	3	22.5	0.9	5
122101900120	RP-5	18-19	4.5	27.5	1.3	5
122102100120	RP-6	20-21	5	35	1.5	10
122102400120	RP-7	22-24	7	42.5	2.2	5
122102700120	RP-8	25-27	8	52.5	2.4	10
122103000120	RP-9	28-30	11	70	3.7	10
122103300120	RP-10	31-33	13	85	4.1	10
122103600120	RP-11	34-36	15	95	5.9	10
122103900120	RP-12	37-39	17	110	6.7	10
122104200120	RP-13	40-42	21	125	9.3	10
122104500120	RP-14	43-45	26	155	10.5	10
122104800120	RP-15	46-48	30	180	12.1	10
122105600120	RP-17	52-56	42.5	240	21.3	10

Lifting table

Combination of the Nomag Rope Pear Socket with Nomag Quick Release Link

A Rope Pear Socket can be fitted to a Quick Release Link of the same size, or to a link with a different size as indicated in table

Pear code:	Link code:
RP-2	
RP-3	RL-4
RP-4	RL-4 / RL-5
RP-5	RL-4 / RL-5 / RL-6
RP-6	RL-5 / RL-6 / RL-7
RP-7	RL-6 / RL-7 / RL-8 / RL-9
RP-8	RL-7 / RL-8 / RL-9
RP-9	RL-8 / RL-9 / RL-10
RP-10	RL-9 / RL-10 / RL-11
RP-11	RL-10 / RL-11 / RL-12
RP-12	RL-11 / RL-12 / RL-13
RP-13	RL-12 / RL-13 / RL-14
RP-14	RL-13 / RL-14 / RL-15
RP-15	RL-14 / RL-15
RP-17	RL-17

Blueprint

