



ELD 168 Swivel hook (underload-light duty)

Product information

Suitable for turning under load. Hook with standard bearings for the most common applications.

Marking: According to standard, CE-marked

Finish: Red painted.

Standard: EN 1677-2

Note: Can rotate with load.

Safety factor: 4:1.

Grade: 8

Part Code	Code	WLL ton	EWL mm	Chain Ø mm	A mm	B mm	C mm	D mm	D1 mm	E mm	F mm	H mm	L mm	M mm	N mm	P mm	R mm	Weight kg	Delivery time
420500130770	168 010 ES	1.25	133	6	10	34	77	24	20	21	15	31	133	38	63	39	12.5	0.75	10
420500160770	168 015 ES	1.6	140	7	10	33	82	26	22	23	18	34	140	38	63	39	12.5	1	10
420500250770	168 020 ES	2.5	163	8	12.5	42	94	27	23	27	23	38	163	47	79	48	16	1.4	5
420500320770	168 030 ES	3.2	172	10	12,5	40	106	32	27	31	23	42	172	47	79	48	16	1.66	5
420500540770	168 045 ES	5.4	213	13	15	50	132	40	35	37	30	50	213	58	96	60	19	3.65	10
420500800770	168 070 ES	8	266	16	17,5	65	165	51	43	49	37	62	266	72	120	70	24	5.87	10
420501150770	168 110 ES	11.5	310	19	22	68	198	58	53	60	43	75	310	82	136	82	27	9.75	10
420501600770	168 150 ES	16	352	22	24	84	222	66	58	67	52	84	352	92	154	92	31	15.3	10
420502200770	168 200 ES	22	434	26	29	107	283	87	78	80	64	110	434	115	191	108	38	26.5	10
420503150770	168 300 ES	31.5	512	32	34	117	339	97	87	94	80	120	512	132	222	132	45	50	10

Blueprint

