



General use



## Steel Wire Rope ROPETEX S42 PVC

### Product information

**ROPETEX**



ROPETEX S42 is a galvanized rope equipped with a Fibre Core (FC) and has a PVC coating. It can be used for various applications such as locking rope, signaling devices, etc but not for lifting. It's most used in small diameters up to 8 mm.

Available with transparent, matt black or a matt Red (RAL 3020) PVC coating.

The PVC coating is UV stabilized which makes it suitable for longterm outdoor use and it is fully compliant with REACH Directive 1907/2006.

**Rope construction:** 6x7 FC

**Marking:** According to standard

**Temperature range:** -30°C up to +70°C

**Standard:** EN 12385-4

*except from coating*

**Warning:** Not to be used for lifting purposes

**Fill factor:** 0,47

Part Code	Rope Diameter, mm	Inner diameter mm	Tensile strength N/mm <sup>2</sup>	Steel area mm <sup>2</sup>	Min. Breaking force kN.	Colour	Finish	Weight kg/100m	Delivery time
105130030020010	3	-	1,770	-	-	-	Galvanized	-	-
105130040020010	4	-	1,770	-	-	-	Galvanized	-	-
105130050030010	5	-	1,770	-	-	-	Galvanized	-	-
105130060040010	6	-	1,770	-	-	-	Galvanized	-	-
105130070050010	7	-	1,770	-	-	-	Galvanized	-	-
105130080060010	8	-	1,770	-	-	-	Galvanized	-	-