



Stay rope



Agriculture and livestock



Steel Wire Rope ROPETEX S19 Stainless Steel

Product information

ROPETEX



ROPETEX S19 is a stainless steel wire rope. It's very corrosion resistant and durable, well suited for marine applications. The S19 rope has very little stretch which makes it excellent for standing rigging, stays, controls and architectural balustrades and green walls.

ROPETEX S19 can be provided with swaged terminals as end fittings.

Rope construction: 1x19

Material: AISI 316 / EN 1.4401

Marking: According to standard

Temperature range: -40°C up to +200°C

Standard: EN 12385-10

except material

Warning: Not to be used for lifting purposes

Fill factor: 0,74

Part Code	Rope Diameter,	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force kN.	Finish	Weight kg/100m	Delivery time
108100101620018	1	1,570	-	-	Stainless	-	-
108100131620018	1.25	1,570	-	-	Stainless	-	-
108100151620018	1.5	1,570	-	-	Stainless	-	-
108100201620018	2	1,570	-	-	Stainless	-	-
108100251620018	2.5	1,570	-	-	Stainless	-	-
108100301620018	3	1,570	-	-	Stainless	-	-
108100401620018	4	1,570	-	-	Stainless	-	-
108100501620018	5	1,570	-	-	Stainless	-	-
108100601620018	6	1,570	-	-	Stainless	-	-
108100701620018	7	1,570	-	-	Stainless	-	-