



Master Link Pewag AWP

Product information

Standard master link for creating I- and II- leg chain slings using the CWP connex connecting links.

Material: Alloy steel

Marking: According to standard, CE-marked, Pewag or PW, winner pro or 12, H16, batch code and type

Temperature range: -60°C up to +300°C

Finish: Light blue powdercoated

Standard: EN 1677-4

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 12

| Part Code | Code | WLL ton | Usable up to sling hooks following DIN 15401 No. | d mm | s mm | t mm | w mm | Weight kg | Delivery time |
|--------------|--------|---------|--|------|------|------|------|-----------|---------------|
| 403100240020 | AWP 13 | 2.36 | 2,5 | 13 | 10 | 110 | 60 | 0.34 | 10 |
| 403100350020 | AWP 16 | 3.5 | 2,5 | 17 | 14 | 110 | 60 | 0.53 | 10 |
| 403100530020 | AWP 18 | 5.3 | 5 | 19 | 14 | 110 | 75 | 0.92 | 10 |
| 403100800020 | AWP 22 | 8 | 6 | 23 | 17 | 160 | 90 | 1.6 | 10 |
| 403101250020 | AWP 27 | 12.5 | 10 | 28 | 21 | 200 | 110 | 2.85 | 10 |
| 403101750020 | AWP 33 | 17.5 | 10 | 33 | 21 | 200 | 110 | 4.14 | 10 |

Blueprint

