



## Chain Block POWERTEX PCB-S1

### Product information

**POWERTEX**



#### Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Compact, lightweight construction.
- Durable all steel construction with powder coated finish and plated frame components.
- Safe, well covered automatic load reaction brake.
- Sealed ball bearings on the chain wheel maximise efficiency and serviceability.
- European made COROLIM<sup>®</sup> protected load chain.
- Corrosion resistance of the chain is equivalent to ISO944-9 C5High / ISO9223 C3
- Bottom hook with ball bearing.
- RFID equipped (chip) for easy service and inspection.
- QR code for on-site access to Multilanguage user manuals.
- User manuals in 14 languages included.
- Fulfills the Machinery Directive 2006/42/EC.
- Comply fully with the EN norms 13157 and 818-7.
- Testcertificate enclosed.

**Marking:** According to standard

**Temperature range:** -10°C up to +50°C.

**Standard:** EN 13157, EN 818-7

**Warning:** Do not overload the brake by prolonged lowering. It may cause brake function to fail.

**Safety factor:** 4:1

Part Code	WLL ton	Lifting height m	Load chain Ø mm	Number of falls	A mm	B mm	C mm	Ø mm	E mm	H mm	Weight kg	Delivery time
500100030300070	0.25	3	4 x 12	1	106	68	108	18	20	280	6.4	5
500100300600070	3	6	10 x 30	1	195	95	226	36	37	435	29.4	10

## Blueprint

