



## ROPETEX Ultra Lube 2

### Product information

#### ROPETEX

Ropetex Ultra Lube 2 is an ecofriendly, advanced high-performance hybrid grease. It is developed to perform in dockside, offshore and deep-water environments. Furthermore, it has superior wash-off performance and is bio-degradable, non-toxic and non-bio accumulative.

Ropetex Ultra Lube 2 is an Environmentally Acceptable Lubricant (EAL) and is fully VGP 2013 compliant. It can therefore be used on docksides, riversides, lakes and other environmental sensitive locations.

Due to the composition of the product, it is stable over a wide temperature range, making it suitable for tropical environments.

**Typical applications:** Offshore cranes, dockside cranes; offshore and harbor installations; subsea installations.

**Application methods:** High pressure equipment or brushing.

**Minimum application temperature:** -5°C (Product should be kept to at least 10°C for 48 hours before application).

**Color/texture:** Matte black grease

**NLGI grade:** 2

**Drop point:** 154°C

**Break point:** -60°C

**Relative density:** 0.9 - 0.95

**Hot salt spray test:** 2880 hours

**4-ball weld load:** > 400 kgf

**4-ball weld scar:** 0,55 mm

**Water spray-off:** < 60% retention

**Environmentally Acceptable Lubricant:** YES

**VGP 2013 compliant:** YES

Available in 12,5 kg pail.

#### Extra:

Do not forget to download the white paper with a lot of useful information about wire rope lubricants. It is free! (see the 'documents' tab).

**Temperature range:** -40°C up to +120°C

Part Code	Description	Weight kg	Delivery time
-----------	-------------	--------------	---------------

142501250050

Ropetex Ultra Lube 2

12.5

10