



ROPETEX Ultra Lube 2

Product information

ROPETEX

Ropetex Ultra Lube 2 is an ecofriendly, advanced high-performance hybrid grease. It is developed to perform in dockside, offshore and deep-water environments. Furthermore, it has superior wash-off performance and is bio-degradable, non-toxic and non-bio accumulative.

Ropetex Ultra Lube 2 is an **Environmentally Acceptable Lubricant (EAL)** and is fully **VGP 2013** compliant. It can therefore be used on docksides, riversides, lakes and other environmental sensitive locations.

Due to the composition of the product, it is stable over a wide temperature range, making it suitable for tropical environments.

Typical applications: Offshore cranes, dockside cranes; offshore and harbor installations; subsea installations.

Application methods: High pressure equipment or brushing.

Minimum application temperature: -5°C (Product should be kept to at least 10°C for 48 hours before application).

Color/texture: Matte black grease

NLGI grade: 2

Drop point: 154°C

Break point: -60°C

Relative density: 0.9 - 0.95

Hot salt spray test: 2880 hours

4-ball weld load: > 400 kgf

4-ball weld scar: 0,55 mm

Water spray-off: < 60% retention

Environmentally Acceptable Lubricant: YES

VGP 2013 compliant: YES

Available in 12,5 kg pail.

Extra:

Do not forget to download the white paper with a lot of useful information about wire rope lubricants. It is free! (see the 'documents' tab).

Temperature range: -40°C up to +120°C

Part Code	Description	Weight kg	Delivery time
-----------	-------------	--------------	---------------

142501250050

Ropetex Ultra Lube 2

12.5

10