



## Stållina rostfri 6x7-WSC

### Produktinformation



**Konstruktion:** 6x7-WSC (49-trådig)

**Material:** AISI 316

**Märkning:** Enligt standard

**Standard:** EN 12385-4

**Fyllnadsfaktor:** 0.55

Allmänt bruk



Staglina



Art.nr	Lindiameter	Trådållfasthet N/mm <sup>2</sup>	Ytbehandling	Rope lay.	Min brottkraft kN	Stålärea mm <sup>2</sup>	Smörjning	Vikt kg/100m
108100104620098	1	1 570	Rostfri	sZ	0,61	0,43	No-Lube	0,38
108100154620098	1,5	1 570	Rostfri	sZ	1,37	0,97	No-Lube	0,86
108100204620098	2	1 570	Rostfri	sZ	2,44	1,73	No-Lube	1,54
108100254620098	2,5	1 570	Rostfri	sZ	3,81	2,7	No-Lube	2,4
108100304620098	3	1 570	Rostfri	sZ	5,48	3,89	No-Lube	3,46
108100404620098	4	1 570	Rostfri	sZ	9,75	6,91	No-Lube	6,14
108100504620098	5	1 570	Rostfri	sZ	15,2	10,8	No-Lube	9,6
108100604620098	6	1 570	Rostfri	sZ	21,9	15,6	No-Lube	13,8
108100704620098	7	1 570	Rostfri	sZ	29,8	21,2	No-Lube	18,8
108100804620098	8	1 570	Rostfri	sZ	39	27,6	No-Lube	24,6