

## Stållina 8x36WS-IWRC

### Produktinformation



**Konstruktion:** 8x36WS-IWRC (337-trådig)

**Märkning:** Enligt standard

**Standard:** EN 12385-4


**Fyllnadsfaktor:** 0.6

**RCN:** 11

Vinschlina



Telfer/ Travers



Tornkran



Art.nr	Lindiameter	Trådållfasthet N/mm <sup>2</sup>	Ytbehandling	Rope lay.	Min brottkraft kN	Stålärea mm <sup>2</sup>	Smörjning	Vikt kg/100m
101101304050091	13	1 770	Blank	sZ	106	79,1	A-1	70,5
101101303050091	13	1 770	Blank	zS	106	79,1	A-1	70,5
101101304250091	13	1 770	Galvaniserad	sZ	106	79,1	A-1	70,5
101101303250091	13	1 770	Galvaniserad	zS	106	79,1	A-1	70,5

101101304070091	13	1 960	Blank	sZ	118	79,1	A-1	70,5
101101303070091	13	1 960	Blank	zS	118	79,1	A-1	70,5
101101304270091	13	1 960	Galvaniserad	sZ	118	79,1	A-1	70,5
101101303270091	13	1 960	Galvaniserad	zS	118	79,1	A-1	70,5
101101404050091	14	1 770	Blank	sZ	124	91,7	A-1	81,7
101101403050091	14	1 770	Blank	zS	124	91,7	A-1	81,7
101101404250091	14	1 770	Galvaniserad	sZ	124	91,7	A-1	81,7
101101403250091	14	1 770	Galvaniserad	zS	124	91,7	A-1	81,7
101101404070091	14	1 960	Blank	sZ	137	91,7	A-1	81,7
101101403070091	14	1 960	Blank	zS	137	91,7	A-1	81,7
101101404270091	14	1 960	Galvaniserad	sZ	137	91,7	A-1	81,7
101101403270091	14	1 960	Galvaniserad	zS	137	91,7	A-1	81,7
101101604050091	16	1 770	Blank	sZ	161	120	A-1	107
101101603050091	16	1 770	Blank	zS	161	120	A-1	107
101101604250091	16	1 770	Galvaniserad	sZ	161	120	A-1	107
101101603250091	16	1 770	Galvaniserad	zS	161	120	A-1	107
101101604070091	16	1 960	Blank	sZ	179	120	A-1	107
101101603070091	16	1 960	Blank	zS	179	120	A-1	107
101101604270091	16	1 960	Galvaniserad	sZ	179	120	A-1	107
101101603270091	16	1 960	Galvaniserad	zS	179	120	A-1	107
101101804050091	18	1 770	Blank	sZ	204	152	A-1	135
101101803050091	18	1 770	Blank	zS	204	152	A-1	135
101101804250091	18	1 770	Galvaniserad	sZ	204	152	A-1	135

101101803250091	18	1 770	Galvaniserad	zS	204	152	A-1	135
101101804070091	18	1 960	Blank	sZ	226	152	A-1	135
101101803070091	18	1 960	Blank	zS	226	152	A-1	135
101101804270091	18	1 960	Galvaniserad	sZ	226	152	A-1	135
101101803270091	18	1 960	Galvaniserad	zS	226	152	A-1	135
101102004050091	20	1 770	Blank	sZ	252	187	A-1	167
101102003050091	20	1 770	Blank	zS	252	187	A-1	167
101102004250091	20	1 770	Galvaniserad	sZ	252	187	A-1	167
101102003250091	20	1 770	Galvaniserad	zS	252	187	A-1	167
101102004070091	20	1 960	Blank	sZ	279	187	A-1	167
101102003070091	20	1 960	Blank	zS	279	187	A-1	167
101102004270091	20	1 960	Galvaniserad	sZ	279	187	A-1	167
101102003270091	20	1 960	Galvaniserad	zS	279	187	A-1	167
101102204050091	22	1 770	Blank	sZ	305	227	A-1	202
101102203050091	22	1 770	Blank	zS	305	227	A-1	202
101102204250091	22	1 770	Galvaniserad	sZ	305	227	A-1	202
101102203250091	22	1 770	Galvaniserad	zS	305	227	A-1	202
101102204070091	22	1 960	Blank	sZ	338	227	A-1	202
101102203070091	22	1 960	Blank	zS	338	227	A-1	202
101102204270091	22	1 960	Galvaniserad	sZ	338	227	A-1	202
101102203270091	22	1 960	Galvaniserad	zS	338	227	A-1	202
101102404050091	24	1 770	Blank	sZ	363	270	A-1	240
101102403050091	24	1 770	Blank	zS	363	270	A-1	240

101102404250091	24	1 770	Galvaniserad	sZ	363	270	A-1	240
101102403250091	24	1 770	Galvaniserad	zS	363	270	A-1	240
101102404070091	24	1 960	Blank	sZ	402	270	A-1	240
101102403070091	24	1 960	Blank	zS	402	270	A-1	240
101102404270091	24	1 960	Galvaniserad	sZ	402	270	A-1	240
101102403270091	24	1 960	Galvaniserad	zS	402	270	A-1	240
101102504070091	25	1 960	Blank	sZ	436	293	A-1	261