



## Kaus K2

### Produktinformation

Extra kraftiga, smidda kaus lämpliga för ställina.

**Material:** Stål.

**Arbetstemperatur:** -20°C upp till +200°C

**Ytbehandling:** Försinkade.

**Anmärkning:** Tolerans : Smidda delar  $\pm 5\%$

Art.nr	Lindiameter mm	A mm	B mm	C mm	D mm	E mm	F mm	Vikt kg/100st	Uppskattad ledtid, upp till
123100800360	8	50,8	42	35	22	9	14	8,2	5
123101000360	9-10	63,5	50	45	30	11	16	10	10
123101200360	11-12	76,2	50	55	35	13	18	20	5
123101300360	13	88,9	73	65	45	15	20	26	10
123101500360	14-15	101,6	75	75	50	17	22	36	10
123101700360	16-17	114,3	85	80	53	19	25	50	5
123101900360	18-19	127	100	90	60	21	29	60	5
123102100360	20-21	139,7	110	95	65	23	33	70	5
123102300360	22-23	152,4	115	120	70	25	34	100	5
123102700360	24-27	177,8	135	140	80	30	38	160	5
123103000360	28-30	203,2	155	160	100	33	44	180	5
123103400360	31-34	228,6	175	185	115	38	49	350	5
123103700360	35-37	254	190	195	120	41	52	440	10
123104200360	38-42	279,4	210	215	130	46	60	520	10
123104700360	43-47	304,8	245	250	145	52	65	730	10
123105400360	48-54	355,6	260	290	155	60	72	1 100	10
123106300360	55-63	431,8	310	370	190	70	84	1 600	10
123107300360	64-73	482,6	350	420	230	81	119	2 750	10
123108300360	74-83	558,8	395	480	255	92	130	3 650	10
123109500360	84-95	606,9	430	540	280	105	145	4 400	10
123110900360	96-109	660,4	450	580	285	120	155	4 700	10

## Ritning & mått

